

MALAYSIA'S LARGEST TAIL LIFT MANUFACTURER



■ MALAYSIA

Powermatics Hydraulics & Engineering (M) Sdn. Bhd.
7, Lengkok Keluli 2, Kawasan Perindustrian Bukit Raja,
41050 Klang, Selangor Darul Ehsan, Malaysia

TEL: (+603) 3344 8000
FAX: (+603) 3344 6000
E-MAIL: sales@powermatics.com

■ SINGAPORE

PH Hydraulics & Engineering Pte. Ltd.
23, Tuas Road, Singapore 638 490

TEL: (+65) 6861 2000
FAX: (+65) 6861 5000
E-MAIL: sales@phgroup.com.sg

www.powermatics.com

TAKE THE LOAD OFF YOUR BACK



- Trusted for practicality by recognised companies in diverse industries
- Designed for a wide variety of applications with diverse technical characteristics
- Customizable to higher load capacities and special designs to suit individual requirements
- Manufactured using only high-quality materials and parts
- Complies with ISO 9001 (International Organization for Standardization)

.....
AVAILABLE IN



STEEL PLATFORM



ALUMINIUM PLATFORM

Model	Capacity (kg)	Min.Floor Height H Min (mm)	Max.Floor Height H Max (mm)	Chassis Width (mm)	Cylinder	
					Lifting	Tilting
PHE - 751	750	810	1170	Min. 750 Max. 850	2	2
PHE - 752	750	840	1230		2	2
PHE - 753	750	875	1300		2	2
PHE - 1001	1000	810	1170	Min. 750 Max. 850	2	2
PHE - 1002	1000	840	1230		2	2
PHE - 1003	1000	875	1300		2	2
PHE 1501	1500	975	1300	Min. 750 Max. 920	2	2
PHE 1502	1500	1090	1550		2	2
PHE 1503	1500	1195	1710		2	2
PHE 2001	2000	975	1300	Min. 750 Max. 920	2	2
PHE 2002	2000	1090	1550		2	2
PHE 2003	2000	1195	1710		2	2

STANDARD FEATURES & ACCESSORIES We only use genuine replacement parts

OPTIONAL FEATURES

SERVICE & REPAIRS




DURABLE HYDRAULIC CYLINDERS

Comes with 4 cylinders for heavy-duty and stable operation

2 single-acting lifting cylinders fitted with safety valves

2 single-acting tilting cylinders

Serviceable to help reduce maintenance cost



CYLINDER PROTECTION COVER

Cylinders fitted with protection cover which prevents scratching on rod and reduce damage of seal



HIGH PERFORMANCE POWERPACK

Fully imported, comply with CE standards

Less weight, high performance

Operates on either 12V or 24V power supply



USER-FRIENDLY CONTROLS

Simple push buttons

Cut-off switch with key

Motor with thermal safety device



SAFETY WARNING FLAGS

Heavy duty UV protected PVC for maximum durability

High-strength reflective strips for high visibility and maximum safety



HEAVY-DUTY PLATFORM ROLLERS

Protects the platform against wear and tear

Protects the floor against damage



AUTO-LEVELING

Automatic platform tilting at ground level

Platform orientation can be adjusted to suit the slope of the ground



FOOT SWITCH

Provides an optional hands free method to control the tail lift platform.

Requires both feet to initiate the movement and release of any control will stop the movement.

This safety feature will prevent unintentional movement of platform.



AFTER SALES SERVICE

We carry a wide range of parts stock for all of our products to minimize service & maintenance downtime